



Femtosecond laser texturing for anti-icing surfaces

17 November 2025, 11:35

Felipe Baroni

A breakthrough in passive ice prevention

Ice accumulation on exposed structures such as aircraft wings, wind turbine blades, pipelines, or offshore platforms remains a persistent challenge in cold environments. Traditional de-icing methods, based on heating or chemical agents, are energy-intensive, costly, and environmentally problematic. At Sirris, we explore femtosecond laser texturing to design surfaces that naturally delay or prevent ice formation.

Understanding how ice forms

Ice forms when water droplets freeze or vapor condenses. To prevent it, we first need to understand wettability how water interacts with a surface.

A droplet can either spread (hydrophilic), bead up (hydrophobic), or barely touch the surface (superhydrophobic). Two states explain these behaviors:

- Wenzel state: the liquid wets the rough surface
- Cassie–Baxter state: the liquid rests partly on air pockets, limiting contact

Achieving a stable Cassie–Baxter state is key for anti-icing. It lets droplets roll off quickly, reducing the time water stays before freezing.




Figure 1 shows this effect: supercooled droplets at $-20\text{ }^{\circ}\text{C}$ remain round and mobile thanks to trapped air pockets, while others already start freezing. A visual proof of delayed nucleation.

When water vapor becomes the enemy

Even a superhydrophobic surface is not automatically icephobic. Ice can form from vapor through frost or condensation. Here, another factor matters: **ice adhesion**. The weaker the bond between ice and the surface, the easier natural forces like wind or vibration can remove it.

At Sirris, we combine femtosecond laser texturing with surface chemistry to tackle both problems. The laser defines micro- and nano-structures, such as pillars or Laser-Induced Periodic Surface Structures (LIPSS), while coatings fine-tune surface energy and freezing behavior. This synergy reduces ice nucleation and limits adhesion once freezing occurs.

Testing in real cold conditions

To evaluate how laser-textured surfaces perform against ice, Sirris launched a series of experiments with the **OWI Lab (Antwerp)** using its advanced climatic chamber. The goal was to measure how different surface designs influence ice nucleation and adhesion under realistic, controlled conditions.


The test campaign included several types of samples:

- Untreated reference surfaces


- Purely coated surfaces
- Micro-textured samples
- Nano-textured (LIPSS) samples
- Hybrid textures combining laser and coating

During controlled sub-zero tests, the samples were exposed to supercooled droplets and repeated frost formation cycles. Observations showed that textured and hybrid surfaces delayed frost spread longer than untreated or coated references. Some designs also showed slower freezing and weaker ice adhesion, suggesting that micro- and nano-scale structuring and its combination with chemical modification is beneficial.

Untreated reference surface



Coated



Nano-textured (LIPSS)



Hybrid texture 1




Figure 2 shows the samples 15 minutes after the test. It is possible to note that LIPSS stands out as the best texture to delay ice formation, while the control and coated samples presents higher ice accretion.

Although results are still preliminary, trends confirm theory: laser-induced topography and its combination with chemical control can significantly delay freezing and ease ice removal.

From lab to industrial scale

The implications reach far beyond the lab. Laser-textured surfaces could enhance safety and efficiency in:

- **Aerospace:** preventing wing icing
- **Wind energy:** keeping blades free from frost
- **Transport:** securing critical infrastructure
- **Offshore operations:** reducing maintenance in harsh weather

Sirris aims to scale this technology for industrial use, ensuring precision, repeatability, and cost-efficiency. Our long-term goal is to integrate passive anti-icing directly into components, improving energy efficiency and extending service life.

Through our partnership with OWI Lab, we bridge scientific innovation and engineering practice, bringing reliable, passive anti-icing closer to industrial reality.



Summary

Femtosecond laser texturing enables surfaces that resist icing naturally. By adjusting micro- and nano-patterns and combining them with coatings, Sirris develops sustainable alternatives to energy-intensive de-icing systems. Early tests confirm strong potential for industrial applications.

Conclusion

The fight against ice is entering a new phase. With femtosecond laser texturing, Sirris demonstrates that passive, durable anti-icing is possible. Continued research and testing will refine this technology turning complex science into practical and scalable innovation for cold-environment industries.

*This article was published as part of the **BBBC project**, with support of the **Belgian FPS Economy**.*

Discover the FEMTOFUNC project

This case study is part of the broader FEMTOFUNC research on biomimetic surface functionality.

Discover the FEMTOFUNC project

Would you like to explore how femtosecond laser texturing can enhance your products' performance in cold conditions?

Contact our surface engineering experts to discuss tailored anti-icing solutions for your application.

[Contact us](#)

Authors



Felipe Baroni